

PL2-510**510gsm Super Tenacity Frontlit Banner****FEATURES**

- ▶ White opaque substrate for high quality frontlit display
- ▶ Super strong, durable with softness & smooth a surface
- ▶ Excellent for long term outdoor billboards & banners

SPECIFICATIONS

- ▶ Item No.
PL2-510
- ▶ Raw Material
100% Polyester
- ▶ Available Width
Up to 5M
- ▶ Ink printability
Solvent
Eco-Solvent
UV
Screen Printing

**APPLICATIONS**

Outdoor Billboards
Long Term Banners



+44(0)161 765 3400
www.soyang.co.uk

For test sample please contact us at to sales@soyang.co.uk
or visit our website at www.soyang.co.uk

PL2-510**510gsm Super Tenacity Frontlit Banner****DESCRIPTION**

White opaque substrate for high quality frontlit display.

Super strong and durable.

Smooth surface with matte finish.

Excellent for long term outdoor billboard and banners.

FEATURES

PVC Free

Phthalate Free

INK PRINTABILITY

SOLVENT

ECO SOLVENT

UV

SCREEN PRINTING

**PROPERTIES****TEST METHOD****METRIC****IMPERIAL**

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	510 g/sq.m	13oz/sq.yd
Base Fabric	DIN 60001	Polyester	
Yarn Dtex	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier
Tensile Strength	DIN EN ISO 1421	1700x1320 N/5cm	191x148 lbs/inch
Tear Strength	DIN 53363	310x268N	70x 60lbs
Adhension	DIN 53357	No delamination	
Flame Resistance	DIN 4102	NFPA 701, B1, M2	
Width	NA	50m	197inch

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.



+44(0)161 765 3400
www.soyang.co.uk

For test sample please contact us at to sales@soyang.co.uk
 or visit our website at www.soyang.co.uk