

SL-BL02**Solar Reinforced Blockout Banner****FEATURES**

- ▶ 1000Dx1000D coated fabric, high tenacity, better strength
- ▶ Printable on both sides with uniform printing quality.
- ▶ W/B/W structure makes it full opacity.
- ▶ Anti-curling, excellent consistency on both sides.

SPECIFICATIONS

- ▶ Item No.
SL-BL02
- ▶ Raw Material
100% Polyester
- ▶ Available Width
Up to 3.2M
- ▶ Ink printability
Solvent
Eco-Solvent
UV
Screen Printing

**APPLICATIONS**

Indoor Double Sided Banners
Roll Up Display Banners
Short Term Outdoor Banners



SOYANG
EUROPE

+44(0)161 765 3400
www.soyang.co.uk

For test sample please contact us at to sales@soyang.co.uk
 or visit our website at www.soyang.co.uk

SL-BL02**Solar Reinforced Blockout Banner****DESCRIPTION**

1000Dx1000D coated fabric, high tenacity, better strength.

W/B/W structure makes it full opacity.

Anti-curling, excellent consistency on both sides.

Can be used as indoor hanging banner, roll up, display, curtain or short time outdoor pole banner, etc.

FEATURES

PVC Free



Phthalate Free

INK PRINTABILITY

SOLVENT



ECO SOLVENT



UV



SCREEN PRINTING

**PROPERTIES****TEST METHOD****METRIC****IMPERIAL**

Total Weight	DIN EN ISO 2286-2, ASTM D751	440 g/sq.m	13oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	
Yarn Dtex	DIN EN ISO 2060, ASTM D 1907	1100 x 1100 dtex	1000 x 1000 denier
Shielding Rate	ANSI PH2.19, ISO 5/2	100%	
Tensile Strength	DIN EN ISO 1421	2800x1600 N/5cm	320x183 lbs/inch
Tear Strength	DIN 53363	440x390 N	99x88 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test 1	DIN 4102-1-B1, NFPA 701 Test 1	
Width	NA	Max 3.2m	126inch
Standard Length	NA	Max 5m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.



+44(0)161 765 3400
www.soyang.co.uk

For test sample please contact us at to sales@soyang.co.uk
or visit our website at www.soyang.co.uk