

# ST-100 Diana Light Soft Backlit Polyester Woven Display Fabric

## FEATURES

- ▶ 100% polyester woven fabric with tight structure
- ▶ Smooth surface, soft hand feel, good wrinkle-resistance
- ▶ Ideal for light box, also can be used as indoor deco, display, etc

## SPECIFICATIONS

- ▶ Item No.  
**ST-100T**
- ▶ Raw Material  
**100% Polyester**
- ▶ Available Width  
**Up to 3.2M**
- ▶ Ink printability  
**Dye-Sub Direct  
Dye-Sub Paper**



## APPLICATIONS

Light Box Graphics  
Retail Display  
Indoor Deco

 **SOYANG**  
EUROPE

+44(0)161 765 3400  
[www.soyang.co.uk](http://www.soyang.co.uk)

For test sample please contact us at to [sales@soyang.co.uk](mailto:sales@soyang.co.uk)  
or visit our website at [www.soyang.co.uk](http://www.soyang.co.uk)

# ST-100 Diana Light Soft Backlit Polyester Woven Display Fabric

## DESCRIPTION

100% polyester woven fabric with tight structure  
Smooth surface, soft hand feel, good wrinkle-resistance  
Ideal for light box, also can be used as indoor deco and retail displays.

### FEATURES



PVC Free

Phthalate Free

Wrinkle Free

### INK PRINTABILITY



DYE Paper

DYE Direct

MEMMENTO



## PROPERTIES

## TEST METHOD

## METRIC

## IMPERIAL

Total Weight	DIN EN ISO 2286-2, ASTM D751	190 g/sq.m	5.6oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060	83x85x55 dtex	75x50x50 denier
Weave Method	N/A	Woven	
Shrinkage	190 °C, 30 secs	≤2%	X-Rite 341C
Light Transmittance	ANSI PH2.19, ISO 5/2	42%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1 EN13501-1	
Recommend Fixation	N/A	°C-190 °C, 1-2min	
Yellowing Temperature	SUPRKC REX-C400, 30 secs	≥210 °C	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty



+44(0)161 765 3400  
[www.soyang.co.uk](http://www.soyang.co.uk)

For test sample please contact us at to [sales@soyang.co.uk](mailto:sales@soyang.co.uk)  
or visit our website at [www.soyang.co.uk](http://www.soyang.co.uk)