



ST-118 Mesh Flag Polyester Knitted Fabric

DESCRIPTION

100% polyester soft textured mesh with semi glossy finish. Suitable for indoor and outdoor applications. Perfect double penetration after Dye-sub printing.

FEATURES





INK PRINTABILITY







PROPERTIES TEST METHOD METRIC IMPERIA

Total Weight	DIN EN ISO 2286-2, ASTM D751	115 g/sq.m	3.4oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100% Polyester	100%Polyester
Weave Method	N/A	Warp Knitted, 3-bar	
Shrinkage	210°C, 30 secs	≤2%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1,	B1 TYPE B	
Recommend Fixation	N/A	190°C, 1-2min	
Yellowing Temperature	SUPRKC REX-C400, 30 secs	≥210°C	
Breaking Load	EN ISO 1412	Warp 95N Weft 206N	
Tear Strength	DIN 53363	Warp 95N Weft 61N	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	100m	110yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

