



COFFEE HOU

ST-301 Horizon Tent

Polyester Woven Coated Fabric

DESCRIPTION

Ideal for promo tents / awnings / shelters and similar applications. FR Certification and Water Repellent.

Can also be used for internal lightboxes in retail environments. Available up to 3.15m wide x 50m.

INK PRINTABILITY













Solvent

PROPERTIES	TEST METHOD	METRIC
------------	-------------	--------

Total Weight	DIN EN ISO 2286-2	260 g/sq.m
Base Fabric	DIN 60001	Polyester
Yarn Dtex	DIN EN ISO 2060	330 x 330 dtex
Weave Method		Woven
White Point (CIE86)	CIE86/ASTME313-00(D65/10,SCI	≤120
Shrinkage		≤2% (190°C, 1min)
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	
Hydrostatic Head	GB/T4744 - 1997	
Recommend Fixation		190°C - 205°C, 1-2 min
Transfer temperature		190°C - 205°C, 1-2 min
Yellowing Temperature	SUPRKC REX-C400	220°C
Width Available		Max 315cm
Standard Length		50m

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty



EE HOUS