ST-704 Sub-Magic Polyester Warp-Knitted Wallcovering

WORK

BE PAT

FEATURES

Dye-sub paper-transfer or direct but also UV and Latex compatible.

Use commercial-grade PVA-type adhesive or similar. Grey reverse promotes excellent opacity.

FR Certification available upon request.

SPECIFICATIONS



 \triangleright

ST-704



Available Width **Up to 3.2M**

Ink printability Dye-Sub Direct Dye-Sub Transfer UV & LATEX

Exhibitions Graphics

Seamless Wall Graphics

APPLICATIONS



For test sample please contact us at to sales@soyang.co.uk or visit our website at www.soyang.co.uk

+44(0)161 765 3400 www.soyang.co.uk

ST-704 Sub-Magic Polyester Warp-Knitted Wallcovering

DESCRIPTION

Dye-sub paper-transfer or direct but also UV and Latex compatible. Use commercial-grade PVA-type adhesive or similar. Ideal for seamless wall decoration and exhibition graphics. Grey reverse promotes excellent opacity. FR Certification available upon request.

Available up to 3200mm in 50m rolls.





TEXTILE

PROPERTIES	TEST METHOD	METRIC
Composition	DIN 60001-3	100% Polyester
Construction	Soyang Technologies test procedure	2-bar Warp Knitted
Mass (gsm)	DIN EN ISO 2286-2	280
Opacity	ANSI PH22. 19, ISO 5/2	96%
Recommended Faxation Temp.	Soyang Technologies	190 - 210C, 60 - 120 secs
(Centigrade, Seconds)	test procedure	
Flame Resistance	BS5867	Туре В

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty



For test sample please contact us at to sales@soyang.co.uk or visit our website at www.soyang.co.uk

+44(0)161 765 3400 www.soyang.co.uk