

# Vinyl BP 550

Knife-coated flex-face back-lit Banner

## FEATURES

- ▶ Low wicking PVC double-coated, high tenacity Polyester fabric, anti-fungal
- ▶ Flame retardant option available
- ▶ Available in a choice of widths up to 5m

## SPECIFICATIONS

- ▶ Item No.  
**Vinyl BP 550**
- ▶ Raw Material  
**75% PVC**  
**25% Polyester**
- ▶ Available Width  
**Up to 5M**
- ▶ Ink printability  
**Solvent**  
**Eco Solvent**  
**UV**  
**Latex**



## APPLICATIONS

**Outdoors Signage**  
**Backlit Banners**  
**Posters**  
**Light boxes**



+44(0)161 765 3400  
[www.soyang.co.uk](http://www.soyang.co.uk)

For test sample please contact us at to [sales@soyang.co.uk](mailto:sales@soyang.co.uk)  
or visit our website at [www.soyang.co.uk](http://www.soyang.co.uk)

# Vinyl BP 550

## Knife-coated flex-face back-lit Banner

### DESCRIPTION

Low wicking PVC double-coated, high tenacity

Polyester fabric, anti-fungal.

Flame retardant option available.

Available in a choice of widths up to 5m.

### INK PRINTABILITY



UV



LATEX



SOLVENT



ECO SOLVENT



### PROPERTIES

### TEST METHOD

### SPECIFICATION

Thickness		0.45
Total Mass (g/m <sup>2</sup> )	EN ISO 2286-2	550 ± 50
Composition		72% PVC 29% Polyester
Fabric Mass (gsm)	EN ISO 2286-2	140 ± 10
Breaking Load (daN/50mm)	EN ISO 1421	Warp:250 Weft:170
Tear Strength	DIN 53363	Warp:14.0 Weft:15.0
Coating Adhesion (daN/50mm)	EN ISO 2411	Min 5.0
Flammability (mm/min)	DIN 4102	B1

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.



+44(0)161 765 3400  
[www.soyang.co.uk](http://www.soyang.co.uk)

For test sample please contact us at to [sales@soyang.co.uk](mailto:sales@soyang.co.uk)  
 or visit our website at [www.soyang.co.uk](http://www.soyang.co.uk)