

UNI 501

Universal PVC Digital Floor Vinyl

FEATURES

- ▶ Quick & Easy To Install
- ▶ Natural Look & Feel
- ▶ Easy To Clean
- ▶ Dirt Repellant
- ▶ Slip Resistant
- ▶ Heat Insulation

SPECIFICATIONS

Item No.
Uni 501



Raw Material
100% Polyester



Available Width
Up to 4M



Ink printability
UV & LATEX

APPLICATIONS

Event Flooring
Exhibition Flooring
Retail Floor Graphics



SOYANG
EUROPE

+44(0)161 765 3400
www.soyang.co.uk

For test sample please contact us at sales@soyang.co.uk
or visit our website at www.soyang.co.uk

UNI 501

Universal PVC Digital Floor Vinyl

DESCRIPTION

A PVC-coated polyester woven cushioned flooring that resembles a linoleum material. It is suitable for retail floor graphics, exhibition flooring and retail displays.

INK PRINTABILITY



UV

LATEX



PROPERTIES

TEST METHOD

METRIC

Euro Classification	EN ISO 10874	Domestic General
Total Thickness	EN ISO 24346	ca. 2,00 mm
Wearlayer	EN ISO 24340	ca. 0,20 mm
Wearlayer Treatment		PU / Natural Feel
Total Weight	EN ISO 23997	ca. 1500 g/m ²
Slip Resistance	EN 13893	DS
Inflammability	EN 13501	Cfl-S1
Acoustical Insulation	EN 717	16 dB
Underfloor Heating	EN 12524	Suitable
Thermal Conductivity	EN 12524	0,25 W/mk
Thermal Resistance	EN ISO 12466	0,0080 m ² K/W
Resistance to Household Chemicals	EN ISO 26987	Very good

NOTE: All the above information shall only be used as a guide; buyers should independently test and determine the products suitability. The mentioned data are the averages of a test result and should not be used for the purpose of a lawsuit or warranty.