

Easymount® is designed to perform and built to last.



▲ EM-1600SH

KEY FEATURES

- 6m/20ft a minute
- Variable speed control
- Foot pedal
- Reverse mode
- Multilingual control panel
- 25mm/1" mounting thickness

GREAT FOR USE IN

- Sign makers
- Print finishers

IDEAL WHEN LAMINATING

- Posters, graphics and signs
- Mounting prints to board
- Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage and many more...

Scan with your smartphone to watch the video



Design & Performance

The Easymount® laminators are designed to perform and built to last.

Their advanced features allow you to laminate and mount.

Designed in-house by Vivid, the Easymount® range gives your business extra capacity by allowing you to offer your customers a complete service that you previously had to outsource.

Features

- Solid heavy duty construction
- Release liner take-up
- Adjustable rollers up to 20mm/0.8"
- Large rollers for even pressure
- Handy reverse mechanism
- Foot pedal for controlled operation

Specifications

	EM-1200SH	EM-1400SH	EM-1600SH	EM-2100SH
Laminating Speed (m/ft/min)	6m/20ft	6m/20ft	6m/20ft	6m/20ft
Max. Width (mm/inches)	1200mm/47"	1400mm/55"	1600mm/63"	2100mm/83"
Mounting Thickness (mm/inches)	25mm/ 1"	25mm/ 1"	25mm/ 1"	25mm/ 1"
Roller Diameter (mm/inches)	112mm/4"	112mm/4"	130mm/5"	130mm/5"
Laminating Temperature (°C/°F)	0-60°C/32-140°F	0-60°C/32-140°F	0-60°C/32-140°F	0-60°C/32-140°F
Control Panel	Digital	Digital	Digital	Digital
Pressure Adjustment	Manual/Gauge	Manual/Gauge	Manual/Gauge	Manual/Gauge
Film Core (mm/inches)	77mm/3"	77mm/3"	77mm/3"	77mm/3"
Power Supply AC (V-Hz)	220/240-50-60	220/240-50-60	220/240-50-60	220/240-50-60
Power Consumption (W)	970	1310	1500	1800
Overall Dimensions (mm/inches)	1790x650x1255mm/ 70x26x49"	1990x650x1255mm/ 78x26x49"	2190x650x1255mm/ 86x26x49"	2650x650x1255mm/ 104x26x49"
Gross Machine Weight (Kg/lbs)	185Kg/408lbs	210Kg/463lbs	245Kg/540lbs	280Kg/617lbs
Warranty	1 year	1 year	1 year	1 year