SL- F06W Greyback Weldable Frontlit Banner

FEATURES

1000x1000, 20x20 base fabric.

Weldable, Greyback, truly eco friendly.

Can be used as banners indoor and outdoor.

SPECIFICATIONS



 \triangleright

SL-F06W



Available Width **Up to 5M**

Ink printability UV & Latex

APPLICATIONS

BANNER

Indoor or Outdoor Banners



For test sample please contact us at to sales@soyang.co.uk or visit our website at www.soyang.co.uk

APRIL

+44(0)161 765 3400 www.soyang.co.uk

SL-F06W Greyback Weldable Frontlit Banner

DESCRIPTION

1000 x 1000, 20 x 20 base fabric, grey back. Truly eco friendly coating. Used for both indoor & outdoor banners.



INK PRINTABILITY

PUCFREE ON THALATE F		OP	
PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	310gsm	9.1 oz per sq ft
Base Fabric	DIN 60001, ASTM D7641	100% Polyester	
Yarn Dtex	DIN EN ISO 2060, ASTM D1907	1100 x 1100 dtex	1000 x 1000 denier
Shielding Rate	ANSI PH2.19, ISO/2	98%	
Tensile Strength	DIN EN ISO 1421	2500 x 2100 N/5cm	286x240 lbs/inch
Tear Strength	DIN 53363	430 x 400N	97 x 90lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Width	DIN EN ISO 3759, ASTM D751-2006	Up to 5m	197inch
Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.



For test sample please contact us at to sales@soyang.co.uk or visit our website at www.soyang.co.uk

+44(0)161 765 3400 www.soyang.co.uk BANNER