



Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

Black Pearl

ST-215UT

BRIEF DESCRIPTION

- 100% polyester fabric with white surface & black back, offers full opacity
- More smooth hand feel with woven structure
- Ideal for backdrop, frame & pop-up

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	260 g/sq.m	7.6 g/sq.m
Base Fabric	DIN 60001, ASTM D7641	100%polyester	100%polyester
Weave Method	N/A		Woven
Shrinkage	ISO 9866-2-1991		≤3%
Shielding Rate	ANSI PH2.19, ISO 5/2		100%
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1		DIN 4102-1-B1, NFPA 701 Test1
Recommend Fixation Temperature	N/A		190°C, 30s
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.