

Onyx

ST-2163

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing

BRIEF DESCRIPTION

- 100% warp-knitted blackback textile with enhanced soft handle
- Full opacity ensures total blockout for exhibition displays
- High stability for UV, Latex and dye-sub printing with brilliant colors
- Slight stretch, truly crease free, easy for transportation and installation
- Up to 5m, can be widely used as backdrops, pop-up, frame, exhibition, display system, etc

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	260 g/sq.m	7.7 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	ISO 9866-2-1991	≤3%	
Shielding Rate	ANSI PH2.19, ISO 5/2	100%	
Flame Resistance	EN13501-1, DIN 4102-1-B1, NFPA 701 Test1	EN13501-1, DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	PD-3200RXD-260	190°C-200°C, 30s-50s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.