FF-330

Anti-Curling Display Film

FEATURES

Perfect product with noncurling at the edge and lay-flat apprearance

Super smooth surface makes it perfect for high-resolution printing and grey back for good opacity

Ideal choice for X displays, roll-up displays, window shop **UP** Tadvertising, posters, hanging decorations.

SUMMER **UP TO 70% OFF**



SPECIFICATIONS

FF-330

Raw Material PET

Available Width **Up to 2.2M**

Ink printability Solvent **Eco-Solvent** UV **Screen Printing**

APPLICATIONS

X Displays **Roll-Up Displays** Window Shop Advertising Hanging Displays



FF-330

Anti-Curling Display Film

DESCRIPTION

Perfect product with non-curling at the edge and lay-flat apprearance.

Super smooth surface makes it perfect for high-resolution printing and grey back for good opacity.

Ideal choice for X displays, roll-up displays, window shop advertising, posters, hanging and decorations.

INK PRINTABILITY





SOLVENT









PROPERTIES	METRIC	IMPERIAL	
Average Weight	330g/sq.m	9.7oz/sq.yd	
Product Structure	0.315mil white surface film+3.74mil transparent		
PET+0.315mil grey back film			
Film Thickness	0.24-0.25mm	9.45-9.84mil	
Available Width	Up to 2.2m	126"	
Regular Length	30/50m	33/55yds	

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

