



## ST-221 Vistex

Polyester Woven Wall Covering 280gsm

## **DESCRIPTION**

New developed fabric with woven textured white surface and rough grey back, both sides with PA coating Application as wall covering with glue on both rough and smooth wall, very easy to use.

Good flatness and perfect opacity, makes it also ideal choice for Roll up, frame, etc



**INK PRINTABILITY** 





one seed 33a tin or take away

METRIC IMPERIAL

| PROPERTIES | TEST METHOD | METRIC |
|------------|-------------|--------|
|------------|-------------|--------|

| Total Weight     | DIN EN ISO 2286-2, ASTM D751    | 330g/sq.m                     | 9.7oz/sq.yd |
|------------------|---------------------------------|-------------------------------|-------------|
| Base Fabric      | DIN 60001, ASTM D7641           | 100% Polyester                |             |
| Weave Method     | N/A                             | Woven                         |             |
| Shielding Rate   | ANSI PH2.19, ISO 5/2            | 99%                           |             |
| Flame Resistance | DIN 4102-1-B1, NFPA 701 Test1   | DIN 4102-1-B1, NFPA 701 Test1 |             |
| Width            | DIN EN ISO 3759, ASTM D751-2006 | Up to 3.2m                    | 126inch     |
| Length           | DIN EN ISO 3759, ASTM D751-2006 | 50m                           | 55yds       |

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

