

ST-225**Blackback warp-knitted polyester fabric****FEATURES**

- ▶ PVC Free.
- ▶ 100% polyester woven fabric coated with blackback.
- ▶ Blackback makes it full opacity and extremely strong.
- ▶ Light weight, soft hand feel and truly crease free for easy folding & handling.
- ▶ Brilliant color output.

SPECIFICATIONS

Item No.
ST-225



Raw Material
100% Polyester



Available Width
Up to 5M



Ink printability
UV
Dye-Sublimation
DIRECT
Dye-Sublimation
PAPER

**APPLICATIONS**

Indoor & short term outdoor use
Backdrop, Pop-up, frame,
Exhibition & Event,
Display system, roller blinds



SOYANG
EUROPE

+44(0)161 765 3400
www.soyang.co.uk

For test sample please contact us at sales@soyang.co.uk
or visit our website at www.soyang.co.uk

ST-225
VBlackback warp-knitted polyester fabric

DESCRIPTION

100% warp-knitted polyester fabric with blackback, full opacity
Light weight, soft hand feel and truly crease free for easy folding & handling.

Brilliant color output with UV inks, also compatible with dye-sub direct and paper transfer.

Highly recommended for indoor and short-time outdoor use as backdrop, Pop-up, frame, exhibition & event, display system, roller blind, sun protection, etc.



INK PRINTABILITY



PROPERTIES

TEST METHOD

METRIC

IMPERIAL

| | | | |
|------------------|--|----------------|-------------|
| Total Weight | DIN EN ISO 2286-2, ASTM D751 | 220g/sq.m | 6.5oz/sq.yd |
| Base Fabric | DIN 60001, ASTM D7641 | 100% Polyester | |
| Weave Method | N/A | Warp-knitted | |
| Shrinkage | 210 °C, 30s | ≤4% | |
| Shielding Rate | ANSI PH2.19, ISO 5/2 | 100% | |
| Flame Resistance | EN13501-1, DIN 4102-1-B1, NFPA 701 Test1 | | |
| Width | DIN EN ISO 3759, ASTM D751-2006 | Up to 5m | 197inch |
| Length | DIN EN ISO 3759, ASTM D751-2006 | 50m | 55yds |

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.



+44(0)161 765 3400
www.soyang.co.uk

For test sample please contact us at sales@soyang.co.uk
or visit our website at www.soyang.co.uk